

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (previously presented) A process for the production of a smoke product, said smoke product being obtained by pyrolysis of an organic material, wherein said process comprises the steps of:

- introducing said organic material to be pyrolyzed in a pyrolysis reactor comprising a substantially hermetically sealed heatable chamber containing at least one rotatable heated endless screw, wherein said heated rotatable screw comprises a heating device that supplies calories to elevate the temperature of the organic material, said material being introduced at one end of said at least one screw,
- heating said organic material in said chamber to a temperature between 300°C and 400°C to pyrolyze said organic material and said organic material moves through said heatable chamber under the influence of rotation of said at least one screw, and
- removing the consumed organic material and recovering the produced smoke from the other end of said at least one screw.

2. (previously presented) The process according to claim 1, wherein the organic material is preheated before being pyrolyzed.

3. (canceled)

4. (previously presented) The process according to claim 1, wherein the produced smoke is condensed at the outlet of the reactor in a condensation device.

5. (previously presented) The process according to claim 1, wherein at least one portion of the pyrolysis gas present at the outlet of the condensation device is re-injected into the reactor.

6. (previously presented) The process according to claim 1, wherein the pyrolysis takes place under precise control, to about 0.1%, of the volume content of oxygen in the reactor.

7. (previously presented) The process according to claim 1, wherein the pyrolysis takes place under precise control, to about one degree Celsius, of the temperature prevailing in said reactor.

8. (previously presented) The process according to claim 1, wherein the pyrolyzed organic material is essentially constituted by wood chips.

9. (previously presented) The process according to claim 1, wherein the pyrolyzed organic material is essentially constituted by fibers or chips of at least one substance selected from the group consisting of wood, cellulose, any other polysaccharide and lignocellulose complex.

10. (previously presented) A method of producing a smoke product, comprising operating a pyrolysis reactor by the process according to claim 1 to produce a smoke product, said pyrolysis reactor comprising a substantially hermetically sealed heatable chamber containing at least one rotatable endless screw comprising a heating device that heats said screw heated by the Joule effect.

11. (previously presented) The method according to claim 10, wherein the product is of liquid smoke.

12. (previously presented) The method according to claim 10, wherein the product is of wood charcoal.

13. (previously presented) Liquid smoke product, obtained by the process according to claim 1, wherein said liquid smoke comprises a volume content of benzopyrene of at most 10 ppb and a volume content of benzoanthracene of at most 20 ppb.

14. (original) Liquid smoke obtained by condensation of smoke according to claim 13.

15. (previously presented) Foodstuff smoked with the smoke according to claim 13.

16. (canceled)

17. (previously presented) A process for the production of a smoke product by pyrolysis of an organic material, comprising:

- introducing said organic material to be pyrolyzed in a pyrolysis reactor comprising a substantially hermetically sealed heatable chamber containing at least one rotatable heated endless screw, wherein said rotatable heated endless screw comprises a heating device that supplies calories to elevate the temperature of the organic material to 300°C to 380°C, said material being introduced at one end of said screw,

- heating said organic material with said at least one rotatable heated endless screw in said chamber at a temperature of 300°C to 380°C to pyrolyze said organic material and said organic material moves through said heatable chamber under the influence of rotation of said at least one screw, and
- removing the consumed organic material and recovering the produced smoke from the other end of said at least one screw.

18. (currently amended) A process for the production of a smoke product obtained by pyrolysis of an organic material, wherein said process comprises the steps of:

- introducing said organic material to be pyrolyzed at one end of at least one rotatable heated endless screw, wherein said at least one rotatable heated endless screw is in a substantially hermetically sealed heatable chamber of a pyrolysis reactor, and wherein said rotatable heated endless screw comprises an electrical heating power device that passes electric current ~~though~~ through the rotatable heated endless screw ~~to heat the organic material to 300°C to 400°C that heats said organic material 300°C to 400°C,~~
- heating said organic material with said rotatable heated endless screw in said chamber at a temperature of 300°C to 400°C to pyrolyze said organic material ~~[[and]]~~ as said

- organic material moves through said heatable chamber under the influence of rotation of said at least one screw, and
- removing the consumed organic material and recovering the produced smoke from the other end of said at least one screw.

19. (currently amended) A process for the production of a smoke product obtained by pyrolysis of an organic material, wherein said process comprises the steps of:

- introducing said organic material to be pyrolyzed at one end of at least one rotatable heated endless screw, wherein said at least one rotatable heated endless screw is in a substantially hermetically sealed heatable chamber of a pyrolysis reactor, and wherein said rotatable heated endless screw comprises an electrical heating device that passes electric current ~~though~~ through the rotatable heated endless screw ~~to heat the organic material to 300°C to 400°C,~~
- heating said organic material with said rotatable heated endless screw in said chamber at a temperature of 300°C to 400°C ~~pyrolyze said organic material~~ as said organic material moves through the substantially hermetically sealed heatable chamber under the influence of rotation of said at least one screw,
- recovering a smoke product from the pyrolyzed organic material, wherein said smoke product is a liquid smoke

comprising a volume content of benzopyrene of at most 10 ppb and a volume content of benzoanthracene of at most 20 ppb, and

- removing the consumed organic material from the other end of said at least one screw.

20. (previously presented) The process according to claim 19, wherein the organic material is dried by preheating before being pyrolyzed.

21. (previously presented) The process according to claim 19, wherein the produced smoke is condensed at the outlet of the reactor in a suitable condensation device.

22. (previously presented) The process according to claim 19, wherein at least one portion of the pyrolysis gas present at the outlet of the condensation device is re-injected into the reactor.

23. (previously presented) The process according to claim 19, wherein the pyrolysis takes place under precise control, to about 0.1%, of the volume content of oxygen in the reactor.

24. (previously presented) The process according to claim 19, wherein the organic material is wood chips.